

**CLEAN COPY**

APP.# 10/624,868

**WHAT IS CLAIMS**

10

CLAIMS 1-22 ( Canceled )

15

20

CLAIM 23 (currently amended) A vacuum excavation method having a means of making dirt or solids vacuum able by using a compressed gas as a means of force in order to propel a volume of liquid to impact said dirt or solid with said liquid and said means of making dirt or solids vacuum able comprising: a container having one or more orifices and one or more valves, and further comprising said container being filled with a gas, and further comprising filling said container with a liquid under pressure thus further compressing said gas to a pressure substantially equivalent to that of said liquid, and further comprising, opening one or more of said valves in order for said gas under pressure to propel said liquid through said orifice and valve and further comprising, said propelled liquid being directed to impact said dirt or solids.

25

CLAIM 24 (currently amended ) A method as described in claim 23 further comprising, providing a diaphragm disposed within said container and further comprising said diaphragm being positioned between said gas and said liquid.

30

35

40

45

CLAIM 25 ( currently amended ) A vacuum excavation method having a means of making dirt or solids vacuum able by using a compressed gas as a means of force in order to propel a volume of liquid and said volume of propelled liquid being directed to impact said dirt or solid thus making said dirt or solids vacuum able and said vacuum excavation method comprising: a container having one or more orifices and one or more valves, and further comprising said container being filled with a gas, and further comprising filling said container with a liquid under pressure thus further compressing said gas to a pressure substantially equivalent to that of said liquid, and further comprising, opening one or more of said valves in order for said gas under pressure to propel said liquid through said orifice and valve and further comprising said propelled liquid being directed to impact said dirt or solid and further comprising a vacuum conduit and said vacuum conduit having a first end of said vacuum conduit positioned in communication with said dirt or solid and a second end of said vacuum conduit being connected to a vacuum producing means.

5 CLAIM 26 (currently amended) A method as described in claim 23 further comprising: positioning a conduit in communication with said valve and orifice whereby said conduit serves to dispense said liquid from said container.

10 CLAIM 27 (currently amended ) A method as described in claim 23 further comprising: having a vacuum conduit and said vacuum conduit having a first end of said vacuum conduit positioned adjacent to said dirt or solid and a second end of said vacuum conduit being adjacently positioned to a vacuum container and further comprising said vacuum  
15 container having a vacuum producing means.

CLAIM 28 (currently amended) A method as described in claim 23 or 25 further comprising: providing a process controller and further comprising said process controller sequencing the opening or closing of said valves,  
20 whereby said controller can sequence the filling of said container with said gas and said liquid and sequence the dispensing of said liquid on a repeatable frequency as desired.

CLAIM 29 (currently amended) A method as described in claim 25  
25 further comprising: providing a diaphragm disposed within said container and further comprising said diaphragm being positioned between said gas and said liquid.

CLAIM 30 (currently amended) A method as described in claim 23 or 25  
30 further comprising: said valve having an actuator and further comprising said valve actuator opening or closing said valve.

CLAIM 31 (currently amended) A method as described in claim 23  
further comprising: said liquid compartment of said container having one  
35 or more dispensing orifices.

CLAIM 32 (currently amended) A method as described in claim 23 or 25 further comprising: positioning a first end of a dispensing conduit in communication with said container orifice or valve, and a second end of  
40 said dispensing conduit having one or more dispensing orifices.

CLAIM 33 (currently amended ) A method as described in claim 25 further comprising: positioning the first end of a dispensing conduit in communication with said container orifice or dispensing valve and the  
45 second end of said dispensing conduit in communication with said dirt or solid.

CLAIM 34 (new) A method as described in claim 23 further comprising: positioning the first end of a dispensing conduit in communication with

5 said container orifice or valve and further comprising, positioning the  
second end of said dispensing conduit in communication with said dirt  
or solids, and further comprising said second end of said dispensing  
conduit being positioned adjacent to a first end of a vacuum conduit and  
further comprising a second end of said vacuum conduit being connected  
10 to a vacuum producing means.

CLAIM 35 (new) A method as described in claim 23 further comprising: a  
vacuum conduit having a first end positioned in communication with  
said dirt or solids and having a second end of said vacuum conduit  
15 adjacently attached to a vacuum producing means and further  
comprising, a liquid dispensing conduit having a first end adjacently  
attached to said container orifice and valve and having a second end of  
said liquid dispensing conduit adjacently positioned in communication  
with said dirt or solids and adjacently positioned in communication with  
20 said second end of said vacuum conduit.

CLAIM 36 (new) A method as described in claim 23 or 25 further  
comprising: disposing within said liquid of said container a positive  
25 electrode and a negative electrode and said positive electrode being  
positioned a distance from said negative electrode and further  
comprising, an electrical current traveling between said negative  
electrodes and said positive electrode whereby said electrical current  
dissipates a portion of it's energy into said liquid as said electrical  
30 current travels between said electrodes, thus converting a portion of the  
liquid into a gaseous phase, thus further increasing the pressure of the  
gaseous propellant.

CLAIM 37 (new) A method as described in claim 23 or 25 further  
35 comprising: passing an electrical current through said liquid in said  
container.

CLAIM 38 (new) A method as described in claim 23 or 25 further  
comprising: passing an electrical current through said liquid in said  
40 container and further comprising a process controller to sequence the  
interaction of said electrical current with said opening or closing of said  
valves.

45